

Godrej Industries Limited

Regd. office: Pirojshanagar, Eastern Express Highway, Vikhroli, Mumbai 400 079. India
Tel: (91-22) 25188010 / 25188020 / 25188030 extn: 4388 Fax: (91-22) 25188096 / 25188068
e-mail: sr.surve@godrejinds.com

LUBOLIC - 20

SPECIFICATIONS

Rev. No. 03, Dtd. 21/01/2013

CARBON CHAIN DISTRIBUTION BY GC (%)

C ₁₆ & Below	C ₁₈	C ₂₀ & Above
6.0 Max	75.0 Min	20.0 Max

PARAMETERS	SPECIFICATIONS
Appearance	: Light Yellow Colour, Clear Liquid
Odour	: Characteristic
Colour 5.25" Lovibond Cell - Red	: 1.5 Max
Colour 5.25" Lovibond Cell - Yellow	: 15.0 Max
Titre °C	: 20.0 Max
Acid Value, mgm KOH/gm	: 195.00 - 200.00
Iodine Value, g I ₂ /100gms	: 145.00 Min
Saponification Value, mgm KOH/gm	: 196.00 - 201.00
% Moisture	: 0.25 Max

Reason for Revision: To correct C20 & above from 9.0 Max to 20 Max.

- Manufactured at Vikhroli & Valia
- Packing :
 - 90 Kg HDPE Carboy
 - 180 Kg HMHDPE Carboy
 - Bulk in Stainless Steel Tanker, ISO & Flexi Container
- Broad Uses:
 - Plastics, Coatings and Inks, Lubricants and Greases
- Kosher Certified